

Test report



No. 2217_FRM

Test object: Photovoltaic flat roof mounting system ValkPro+ L10° South

(reduced size model, appr. 700 x 450 x 250 mm); manufacturer

Van der Valk Solar Systems

incl. UNI Earthing Clamps (Part-No. 540 260) with aluminium

round wire (Ø 8 mm); manufacturer DEHN

Applicant: Van der Valk Solar Systems B.V.

Westernesse 18 2635 BG Den Hoorn The Netherlands

Type of testing:

 Test of the lightning impulse current carrying capability of the test classification N (50 kA) following the principles of IEC 62561-1:2017-03 (Edition 2.0), chapter 6.3.1 and chapter 6.4.

• Evaluation of the PV flat roof mounting system as natural down-conductor of a lightning protection system, following the principles of IEC 62305-3 Edition 2.0 2010-12, chapter 5.3.5.

Test result:

The test of the lightning current capability of the photovoltaic flat roof mounting system ValkPro+ L10° South for the test classification N (50 kA) <u>passed</u> the criteria of IEC 62561-1.¹⁾ The test samples show no visible damages.

➤ The assessment of the photovoltaic flat roof mounting system according to IEC 62305-3:2010-12 (Edition 2.0); chapter 5.3.5, for the compliance with the minimum dimensions is made by the applicant, see Annex A.

Report:

76 pages test report including 36 figures, 9 oscillograms and 3 annexes. Available upon request at Van der Valk Solar Systems.

Neumarkt, 28th March 2022

Markus Fritscher

Bernd Moosburger

Tobias Meyer

Revision:

Senior Technician

Senior Engineer

Head of DEHN Test Centre

1) DEHN UNI Earthing Clamps installing at the ends of the roof carrier profiles, must be positioned as shown on page 9, Figure 3!