



## Datasheet **ValkPro+** on green roofs

### Concept

The ValkPro+ system can also be used on green (sedum) roofs. The system stays intact (see datasheet ValkPro+) without any modifications except for the tile that needs to be placed underneath the rubber tile carrier for a stable base of the system.

### Technical specifications

- Both ValkPro+ South as ValkPro+ East-West possible.
- Under each rubber tile carrier a tile (30x30 cm) needs to be placed. This tile needs to be buried into the green roof so that the top surface of the tile is level with the breeding ground of the sedum. The gap between the rear wind shield and the breeding ground may not exceed 105mm.
- All further system specifications and ballast stay equal with other roof types.
- System calculations can be done with the ValkPVplanner [www.valkpvpplanner.com](http://www.valkpvpplanner.com)



### CONTACT DETAILS | DEVELOPER AND PRODUCER OF SOLAR MOUNTING SYSTEMS

#### Van der Valk Solar Systems + International

Westernesse 18 - 2635 BG Den Hoorn, The Netherlands  
+31 174 25 49 99  
[sales@valksolarsystems.com](mailto:sales@valksolarsystems.com)

#### Valk Solar Systems UK + IE

+44 1304 89 76 58  
[sales@valksolarsystems.co.uk](mailto:sales@valksolarsystems.co.uk)

#### Valk Solar Systems Ibérica

+34 699 326 544  
[ventas@valksolarsystems.es](mailto:ventas@valksolarsystems.es)

#### Valk Solar Systems Nordics

+46 7 25 27 00 66  
[sales@valksolarsystems.se](mailto:sales@valksolarsystems.se)